

**Series 2, Slideout rangehood, 60 cm,
Silver metallic
DFM064W54A**



DSZ4686	Handle strip black
DWZ1IT1B4	Clean Air Standard odor filter (repl.)
DWZ1IT114	Clean Air Standard recirculation kit
DSZ4545	Standard recirculation kit
DSZ4551	Standard odor filter (replacement)
DSZ4682	Handle strip white

**Slideout rangehood: barely visible
integrated in the wall unit, this ensures a
sleek and clear kitchen finish.**

- **3-Speed Power Level Options To Suit Your Cooking Style And Recipes**
- **Dishwasher-safe metal grease filters for easy cleaning.**
- **Grease filtration level: filters out over 85% of the grease from kitchen air**
- **LED lighting: for perfect, energy-efficient illumination of the cooktop.**
- **With exhaust, the air is cleaned by a grease filter and then ducted to the outside which ensures optimal kitchen air quality.**

Typology: Pull-out
 Length electrical supply cord: 175.0 cm
 Min. required niche size for installation (HxWxD): 162mm x 526.0mm x 290mm mm
 Minimum distance above an electric cooktop: 600 mm
 Minimum distance above a gas cooktop: 650 mm
 Net weight: 8.9 kg
 Type of control: mechanical
 Number of power settings: 3
 Max. air extraction: 388 m³/h
 Max. air recirculation: 257 m³/h
 Number of lights: 2
 Noise level: 67 dB(A) re 1 pW
 Diameter of air outlet: 120 / 150 mm
 Grease filter material: Washable aluminium
 EAN code: 4242005252435
 Connection rating: 108 W
 Fuse protection: 10 A
 Voltage: 220-240 V
 Frequency: 50 Hz
 Plug type: AU plug
 Installation typology: Built-in



Series 2, Slideout rangehood, 60 cm, Silver metallic DFM064W54A

**Slideout rangehood: barely visible
integrated in the wall unit, this ensures a
sleek and clear kitchen finish.**

-
- Appliance width: 598 mm
 - Install into a 60cm wide wall cupboard
 - Suitable for ducted or re-circulated extraction
 - Accessory required for recirculation mode: Standard recirculation kit

Design

- Appliance colour: Steel body, metallic finish

Comfort

- 3 power settings
- rocker switch for power and light
- Automatic On/Off operation when telescopic canopy is pulled out and pushed back
- 2 x 1.5W LED
- Colour Temperature: 3500 K

Cleaning

- Dishwasher safe metal grease filters
- Cassette with alu frame

Performance

- Extraction rate exhaust air according to EN 61591: max. 389 m³/h
- Noise min./max. Normal Level: 59/67 dB
- Average Energy Consumption: 40.3 kWh/year
- 1 single inlet horizontal, Capacitor motor

Planning and installation information

- Appliance dimensions (HxWxD): 203 x 598 x 290 mm
- Built-in dimensions (HxWxD): 162 x 526 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Electrical cable length 1.75 m

Consumption Data

- Power rating: 108 W

**Series 2, Slideout rangehood, 60 cm,
Silver metallic
DFM064W54A**



